
time-series-metadata Documentation

Maximilian Gruber, Björn Ludwig, Bang Xiang Yong, Benedikt See

Aug 31, 2022

Getting started:

1	time-series-buffer - a metrological time-series buffer	3
2	TimeSeriesBuffer - the reference	5
3	Indices and tables	7
	Python Module Index	9
	Index	11

time-series-buffer is a Python software package developed by software developers and researchers from [Physikalisch-Technische Bundesanstalt](#) (Germany) as part of the joint European Research Project [EMPIR 17IND12 Met4FoF](#)¹ and the German research project [FAMOUS](#)².

For the *time-series-buffer* homepage go to [GitHub](#)³.

time-series-buffer is written in Python 3 and strives to run with all Python versions with upstream support⁴. Currently it is tested to work with Python 3.5 to 3.8.

[Python package](#)⁵ [Documentation Status](#)⁶

¹ <https://met4fof.eu>

² <https://famous-project.eu>

³ <https://github.com/PTB-PSt1/time-series-buffer>

⁴ <https://devguide.python.org/#status-of-python-branches>

⁵ <https://pypi.org/project/time-series-buffer/>

⁶ <https://time-series-buffer.readthedocs.io/en/latest/>

CHAPTER 1

time-series-buffer - a metrological time-series buffer

This package provides support for time-series buffering based on the build-in Python `collections.deque`.

The package is developed and maintained at the “Physikalisch-Technische Bundesanstalt” by Björn Ludwig and Maximilian Gruber.

TimeSeriesBuffer - the reference

class `time_series_buffer.buffer.TimeSeriesBuffer` (*maxlen=10, return_type='array'*)

Custom buffer class, that allows to save streams of time-series with uncertainty in timestamps and values. Acts like a FIFO buffer.

add (*data=None, time=nan, time_unc=0.0, val=nan, val_unc=0.0*)

Append one or more new datapoints to the buffer. A datapoint consists of the tuple (time, time_uncertainty, value, value_uncertainty).

Parameters

- **data** (*iterable of iterables with shape (N, M) (default: None)*) – If given, all other kwargs are ignored.
 - M==2 (pairs): assumed to be like (time, value)
 - M==3 (triple): assumed to be like (time, value, value_unc)
 - M==4 (4-tuple): assumed to be like (time, time_unc, value, value_unc)
- **time** (*float, or iterable of float/ufloat (default: np.nan)*) – Timestamp(s) to be added.
- **time_unc** (*float, or iterable of float (default: 0.0)*) – Uncertainty(ies) of the timestamp(s) to be added.
- **val** (*(iterable of) float/ufloat (default: np.nan)*) – Value(s) to be added.
- **val_unc** (*(iterable of) float (default: 0.0)*) – Uncertainty(ies) of the value(s) to be added.
- **time_unc, val, val_unc need to be of same shape, but uncertainties can be omitted. (time,)** –

pop (*n_samples=1*)

Return the next *n_samples* from the left side of the buffer.

View the latest *n* additions to the buffer. Returns the format that was specified during init of the buffer.

Parameters `n` (*int* (default: 1)) – How many datapoints to return.

Returns

Return type Depends on `return_type`, see `__init__()` for details

show (*n_samples=1*)

View the latest *n_samples* additions to the buffer. Returns the format that was specified during init of the buffer.

Parameters `n_samples` (*int* (default: 1)) – How many samples to return. Return all samples in buffer, if set to -1.

Returns

Return type Depends on `return_type`, see `__init__()` for details

CHAPTER 3

Indices and tables

- `genindex`
- `modindex`
- `search`

t

`time_series_buffer.buffer, 5`

A

`add()` (*time_series_buffer.buffer.TimeSeriesBuffer*
method), 5

P

`pop()` (*time_series_buffer.buffer.TimeSeriesBuffer*
method), 5

S

`show()` (*time_series_buffer.buffer.TimeSeriesBuffer*
method), 6

T

`time_series_buffer.buffer` (module), 5

`TimeSeriesBuffer` (class in
time_series_buffer.buffer), 5